

HORECATECH

MACCHINA PER SOTTOVUOTO A CAMPANA

// CHAMBER VACUUM SEALER

Corpo macchina in acciaio inox • Adatta al confezionamento di solidi e liquidi • Adatta per buste lisce e goffrate • Ferma buste integrato • Barra saldante estraibile da 410 mm con doppia saldatura (4 mm x 2) • Vasca stampata concava in lega di alluminio • Cicli regolabili (sottovuoto, saldatura e raffreddamento) • Sollevamento campana automatico a fine ciclo • Campana in plexiglass da 25 mm • Manometro • Display digitale • Dotata di due pannelli in teflon • Pompa ad olio (dosatore e prima carica in dotazione da caricare al primo utilizzo)

S/S Machine body • Suitable for solids and liquids • Suitable for smooth and embossed envelopes • Integrated envelope holder • 410 mm removable sealing bar with double welding (4 mm x 2) • Concave molded tank in aluminum alloy • Adjustable cycles (vacuum, sealing and cooling) • Automatic bell lifting at the end of the cycle • 25 mm plexiglass bell • Oil pump (doser and first load supplied to be loaded on the first use) • Gauge • Digital display • Equipped with two teflon panels



Carrozzeria in acciaio inox
S/S Machine Body

REF.
RS673



8 056518 695988



DIMENSIONI/SIZE

49 x 55 x 45 (H) cm



DIMENSIONI CAMERA/CHAMBER SIZE

49 x 55 x 18 (H) cm



PESO/WEIGHT

53 Kg



DATI ELETTRICI/ELECTRICAL FEATURES

220 - 240V ~ 50HZ - 1100W

Portata pompa <i>Pump Speed (Max)</i>	360 l /min - 22 mc/h
Olio Pompa <i>Pump oil</i>	ISO VG 46
Dimensioni imballo <i>Packaging size</i>	1 pz 68 x 61 x 60 cm imballo in cassa in legno/packaging in wooden case

